

Sterling Anniversary EL 34 H/W



Sterling Anniversary EL 34 H/W (single ended) (kod-AUD0010)

Audion Sterling Anniversary integrated stereo is hard wired point to point using better graded components and & larger Audion wound output transformers (EI96) & hand built. This pentode based EL34 stereo amp uses a small amount of feedback in the design. The chassis is black powder coated aluminum as is the transformer cover. The top plate and badge are mirror finished stainless steel.

This combination makes for smooth transients, good signal handling and tight response curves. There is an audible difference with the Anniversary products, due to the larger transformers and better grade components over the Mk1 printed circuit board models

Amplifier matching

This Sterling is suited for use with loudspeakers of 89db or better efficiency. Ideally matched with our range of Proton cables. The amp delivers 12 watts into 8 ohms. It can be changed internally to work with 4 ohm loudspeakers too. Our integrated model comes with 5 line level



inputs and a straight thru tape output switched from the front panel. Options are available for this model, see upgrade options at end.

Quality both inside and out

Having a volume control on the front and 5 stereo inputs on the rear means that a pre-amplifier is not necessary with this unit, unless a phono stage is needed.

The amp is auto biased. It will take almost any EL34 (Unit is supplied with Electro Harmonix tubes)

The Sterling is a good entry level hard wired (Air Wired©) Class A power amplifier, sonically very airy with good response. Integrated option (Standard stereo input is available)

The Integrated Sterling is built with components sourced from Europe and the US. Where possible we avoid the use of any Chinese component. Our output transformers are wound in-house to our exacting standards and many of the components are either made by us or specifically for us. We use Electro Harmonix EL34 and Russian New old stock 6H1N as a driver and input tubes.

Power	2 x 12 Watts Class A into 8 Ohms at 240V AC
Sensitivity Ref Load	200mV 8 Ohm
Distortion @ 1Watt	<0.1%
Frequency Response	14 > 40 KHz ±1 dB RIAA
Signal to Noise	< -85 dB
Consumption	140 Watts
Tubes	2 x EL34, 2 x 6H1N
Size	42 cm deep, 23 cm wide and 19 cm tall- less tubes
Weight	14 kg
Fuses	Power 500mA / 240V
Warranty	2 years - tubes 6 months